

TGA & CO Professional Business & Technological Consultancy  
LIGHT CRUDE OIL SPECIFICATIONS



CHARACTERISTICS	UNITS	RESULT	TEST METHOD
Specific Gravity @ 15.67/15	---	0.8568	ASTM D5002
API Gravity	*API	33.6	ASTM D5002
Sulfur Content (Total)	wt. %	1.46	ASTM D4294
H <sub>2</sub> S Content	ppm	86	IP 570
Mercaptan Content	ppm	60	UOP 163
Nitrogen Content(Total)	wt. %	0.13	ASTM D 5762
Water & Sediment	Vol. %	<0.05	ASTM D4007
Water Content	Vol. %	<0.025	ASTM D4006
Salt Content	PTB	7	ASTM D3230
Kinematic Viscosity@ 10°C	mm <sup>2</sup> /S	19.5	ASTM D445
Kinematic Viscosity @ 20°C	mm <sup>2</sup> /S	10.88	
Kinematic Viscosity @ 40°C	mm <sup>2</sup> /S	6.319	
Pour Point (Upper)	°C	-12	ASTM D5853
Reid Vapor Pressure	psi	8.95	ASTM D323
Asphaltene Content	wt. %	1.6	IP 143
Wax Content	wt. %	4.8	BP 237
Drop Melting Point of Wax	°C	57	IP 133
Conradson Carbon Residue	wt. %	4.50	ASTM D189
Total Acid Number	Mg KOH/g	0.12	UOP 565
Nickel Content	mg/kg	11	ASTM D5863
Vanadium Content	mg/kg	40	
Iron Content	mg/kg	<1	
Lead Content	mg/kg	<1	
Sodium Content	mg/kg	8	
Zinc Content	mg/kg	<1	
Copper Content	mg/kg	<1	